

COPPERCATHODE SPECIFICATION



Rectangular plates of electrolytic copper with a high degree of purity.

APPLICATIONS

Its chief application is raw material for the production of electrolytic copper rebar, computer bars, and the composition of various alloys.

CHARACTERISTICS

CHEMICAL COMPOSITION

Material: Electrolytic copper 99.99%.

Chemical Composition: Total concentration of all impurities ≤ 65 ppm (typical value ≤ 25 ppm).
Copper obtained by the difference between 100% and total impurities.

ELEMENT	SPECIFIED	TYPICAL
Se	<1.0 ppm	<1.0 ppm
Te	<1.0 ppm	<0.5 ppm
Bi	<0.5 ppm	0.20 ppm
Sb	<1.0 ppm	<1.0 ppm
As	<3.0 ppm	1.2 ppm
Pb	<1.0 ppm	0.3 ppm
Fe	<5.0 ppm	2.8 ppm
S	<10.0 ppm	4.5 ppm
Ni	<5.0 ppm	<1.0 ppm
Sn	<1.0 ppm	<0.5 ppm
Ag	<12.0 ppm	8.0 ppm

Stack General Groups of Companies

Dar es Salaam, Tanzania

☎ +255 746 358 889

<https://stackengroupcoltd.com/>

COPPERCATHODE SPECIFICATION

ELEMENT	SPECIFIED	TYPICAL
Zn	not specifed	<1.0 ppm
Co	not specifed	<0.5 ppm
Cr	not specifed	<0.5 ppm
Mn	not specifed	<0.5 ppm
O2	100-600ppm	200 ppm

The value specified is in accordance with standard ASTM B115-00



DIMENSIONALASPECT

Length=990±10 mm
Width=970 ± 10mm
Thickness=5 a25 mm

Note: These data are merely illustrative, and release of the product is not contingent upon them.

SURFACEAPPEARANCE

The surface of the cathode should be reasonably free of nodules and foreign matter, such as copper sulfate, grease, oil and sludge residue.

SPECIFICPROPERTIES

Electricconductivity:100%IACS(minimum) Spiral
length = 350 mm (minimum)

Stack General Groups of Companies

Dar es Salaam, Tanzania

☎+255 746 358 889

<https://stackengroupcoltd.com/>

COPPERCATHODE SPECIFICATION

IDENTIFICATION

Cathode packages are identified by four fastening seals with the initials CbM. On the upper plate there is a label, and/or the following data are written:

- Lot/group number
- Package number
- Package plate number
- Net weight of package in kilos

The layouts and identification of CbM cathode packages have part of the plates with flaps in opposing positions, and flaps in matching positions.



CONTAINERS

Each package of cathode weighs from 2,300 to 3,000 kilos, and is bound by two metal ribbons.

SAFETYASPECT

The product is characterized as general freight. It should be handled with leather gloves, with the observance of standards for the movement of heavy-weight freights.

APPLICABLETECHNICALSTANDARDS

The product meets the following technical standards:

- ASTM B115-00
- BSEM1978:1998
- NBR5026-2001

Stack General Groups of Companies

Dar es Salaam, Tanzania

☎ +255 746 358 889

<https://stackengroupcoltd.com/>